



# SILTECH CORP.

## Safety Data Sheet

Prepared in accordance with GHS standard  
& Annex II - EC regulation 1907/2006 and amendments

Silamine DG-50  
SDS No: 6006

Last Revision Date: January 08, 2014

### SECTION 1. IDENTIFICATION

**Material Identification:** Silamine DG-50

**Chemical Name:** Amino functional polydimethylsiloxane in  
aliphatic solvent and isopropanol

**Chemical Classification:** Silicone

**CAS#:** 71750-80-6 / 8052-41-3 / 67-63-0

**Company Identification:**

Siltech Corp.  
225 Wicksteed Avenue  
Toronto, Ontario  
Canada  
M4H 1G5  
(416) 424-4567

**Recommended Product Usage**

Silicone Surfactant  
Coatings

**CANUTEC 24-HOUR EMERGENCY RESPONSE TELEPHONE NUMBER: (613) 996-6666**

USE IN CASE OF A DANGEROUS GOODS EMERGENCY

### SECTION 2. HAZARD(S) IDENTIFICATION

**HAZARD CLASSIFICATION:**

Flammable liquid:	Category 2
Eye Irritation:	Category 2A
Skin Irritation:	Category 2
Specific Target Organ Toxicity (single exposure):	Category 3
Hazardous to the aquatic environment, chronic:	Category 2

**GHS LABEL ELEMENTS** (including precautionary statements):

Symbol :



Signal Word:

Danger

Hazard Risk Statement:

H226: Flammable liquid and vapour.  
H315: Causes skin irritation.  
H319: Causes eye irritation.  
H336: May cause drowsiness or dizziness.  
H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement:

P210: Keep container tightly closed and away from ignition sources such as heat, sparks and open flame. NO SMOKING.

Prevention:

P240: Ground all equipment and use only non-sparking tools.  
P280: Wear suitable protective clothing, gloves and eye protection.

Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P303 + P361+P353: IF ON SKIN: Remove/Take off immediately all contaminated clothing.  
Rinse skin with water/shower.

Storage:

P403 + P233: Store in well-ventilated place. Keep container tightly closed.

Disposal:

P501: Dispose of contents/container in accordance with local / regional / national / international regulations.

**OTHER HAZARD** (risk not included in classification):

CAUTION: Methyl alcohol forms on contact with water or humid air. Provide adequate ventilation.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Common Name or Synonym</u>	<u>CAS No.</u>	<u>EINECS/ELINCS No.</u>	<u>% (w/w)</u>	<u>GHS Classification</u>	<u>Classification according to Directive 67-548/EEC</u>
Aliphatic petroleum distillate	Stoddard solvent	8052-41-3	232-489-3	30 - 40	Flammable liquids: Category 3 Aspiration hazard: Category 1 Skin irritation: Category 2 Specific target organ toxicity - (single exposure): Category 3 Hazardous to the aquatic environment - (chronic): Category 2	Xn R45 R46 R65
2-Propanol	Isopropyl alcohol	67-63-0	200-661-7	10 - 20	Skin Irritation: Category 3 Specific target organ toxicity 6 (single exposure): Category 3 Flammable liquid: Category 3 Eye irritation: Category 2A	Xi, F R11, R26

Other ingredients not listed in this section are non-hazardous or business confidential.

### SECTION 4. FIRST AID MEASURES

**Eyes:** Immediately flush with water. If irritation persists, obtain medical attention.

**Skin:** Wash off with soap and water. If irritation persists, obtain medical attention.

**Inhalation:** Immediately remove to fresh air. Give oxygen for breathing difficulty. If breathing has stopped give artificial respiration. If breathing and pulse are absent give CPR. Immediately obtain medical attention. Stay with casualty until medical assistance is reached.

**Ingestion:** DO NOT INDUCE VOMITING. If patient is fully conscious and not convulsing, give 2 to 4 glasses of water to dilute the material. Transport to medical facility. If spontaneous vomiting occurs have victim lean forward to avoid breathing in of emesis. Rinse mouth and administer more water.

### SECTION 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:** Carbon dioxide, dry powder, foam, or water spray. Water can be used to cool fire exposed containers.

**Unsuitable Extinguishing Media:** None known.

**Specific Hazards Arising from the Chemical:** Silicon Dioxide. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

**Special Protective Actions for Fire-Fighters:** Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. Use water spray to cool fire exposed containers.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions and Protective Equipment:** Avoid eye and skin contact. Use personal protective equipment.

**Environmental Precautions:** Prevent from entering drains or water sources.

**Containment/Clean up:** Collect for disposal. Clean up remaining materials from spill with suitable absorbent. For large spills provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean area as appropriate since some silicone material, even in small quantities, may present a slip hazard. Final cleaning may require steam, solvents or detergents.

## SECTION 7. HANDLING AND STORAGE

**Handling Precautions:** Avoid eye and skin contact. Do not take internally. Use with adequate ventilation. Wash after handling. Exercise good industrial hygiene practice.

**Storage Conditions:** Keep container tightly closed and away from heat, sparks, and flame. Ground all equipment. Static electricity will accumulate and may ignite vapours.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### OCCUPATIONAL EXPOSURE LIMIT VALUES / BIOLOGICAL LIMIT VALUES:

#### Industrial Hygiene Standards

<u>Ingredient</u>	<u>CAS No.</u>	<u>Exposure Limit</u>
Stoddard solvent	8052-41-3	OSHA PEL: TWA 500ppm / ACGIH TLV: TWA 100ppm
Isopropanol	67-63-0	STEL: 500 ppm (15 min) / TWA: 400 ppm (8 hr)

#### ENGINEERING CONTROLS:

Local Ventilation: Recommended.

General ventilation: Recommended.

#### PERSONAL PROTECTIVE EQUIPMENT:

Respiratory protection: In the case of vapour formation use a respirator with an approved filter.

Hand protection: Chemical protective gloves should be worn for repeated or prolonged contact.

Eye protection: Safety glasses should be worn.

Skin protection: Protective equipment is not normally required.

Hygiene measures: Observe good industrial hygiene practices. Wash after handling.

**Note:** These precautions are for room temperature handling. Use at elevated temperatures or aerosol spray applications may require added precautions.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

<u>Appearance:</u>	Hazy Liquid	<u>Viscosity@25°C:</u>	100 – 200 cps
<u>Colour:</u>	Colourless to Yellow	<u>Melting/Freezing Point:</u>	Not determined
<u>Odour:</u>	Kerosene-like	<u>Initial Boiling Point:</u>	Not determined
<u>Odour Threshold:</u>	Not determined	<u>Boiling Range:</u>	Not determined
<u>Flash Point:</u>	13°C (Pensky-Martens closed cup)	<u>Explosive Properties:</u>	No
<u>Flammability:</u>	Not determined	<u>Vapour Pressure @25°C:</u>	Not determined
<u>Flammability Limits:</u>	Not determined	<u>Vapour Density</u>	Not determined
<u>Auto-ignition Temperature:</u>	Not determined	<u>Partition Coefficient</u>	Not determined
<u>Decomposition Temperature:</u>	Not determined	<u>pH:</u>	Not determined
<u>Specific Gravity @25°C:</u>	0.876	<u>Oxidising Properties:</u>	No
<u>Solubility in Water:</u>	Insoluble	<u>Evaporation Rate:</u>	Not determined

## SECTION 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** None known.

**Incompatible Materials:** Strong oxidizing material can cause a reaction. Water can cause methyl alcohol to form.

**Hazardous Decomposition Products:** The following decomposition products may form during fire or at very high temperatures: Carbon Oxides, Silicon dioxide, Formaldehyde, and traces of incompletely burned carbon compounds.

## SECTION 11. TOXICOLOGICAL INFORMATION

### LIKELY ROUTES OF EXPOSURE:

<b>Respiratory:</b>	Exposure is expected.
<b>Oral:</b>	Exposure is expected.
<b>Eye, Skin:</b>	Exposure is expected.

### INFORMATION ON THE HEALTH HAZARDS:

#### **Acute Toxicity:**

<b>Eyes:</b>	Direct contact may cause temporary redness and discomfort.
<b>Skin:</b>	<b>Stoddard Solvent</b> (LD50 Dermal ó rabbit > 3000 mg/kg)
<b>Inhalation:</b>	<b>Stoddard Solvent</b> (LC50 Oral ó rat > 5500 mg/m <sup>3</sup> ó 4hr)
<b>Ingestion:</b>	<b>Stoddard Solvent</b> (LD50 Oral ó rat > 5000 mg/kg)

#### **Chronic Toxicity:**

<b>Skin:</b>	No known applicable information.
<b>Inhalation:</b>	No known applicable information.
<b>Ingestion:</b>	Repeated ingestion or swallowing large amounts may injure internally.
<b>Other Health Hazard</b>	No known applicable information.

**Skin Corrosion/Irritation:** **Isopropanol (rabbit: mild irritant)**

**Serious Eye Damage/Irritation:** **Isopropanol (rabbit: moderate to severe irritant)**

**Respiratory Sensitization:** No known applicable information.

**Skin Sensitization:** No known applicable information.

**Carcinogenicity:** No known applicable information.

**Germ Cell Mutagenicity:** No known applicable information.

**Reproductive Toxicity:** No known applicable information.

**Specific Target Organ:** No known applicable information.  
(Systemic Toxicity ó Single exposure)

**Specific Target Organ:** No known applicable information.  
(Systemic Toxicity ó Repeated exposure)

**Aspiration Hazard:** No known applicable information.

## SECTION 12. ECOLOGICAL INFORMATION

### ECOTOXICITY:

#### Environmental Effects

**Acute:** Not available

**Chronic:** Not available

### PERSISTENCE AND DEGRADABILITY:

**Degradation:** In soil, siloxanes are degraded. The organic solvent is biodegradable.

**Environmental Fate and Distribution:** Siloxanes are removed from water by sedimentation sewage or binding to sludge. Organic solvents may evaporate into atmosphere and degrade.

### BIOACCUMULATIVE POTENTIAL:

**Bioaccumulation:** No bioaccumulation potential.

### MOBILITY IN SOIL:

None known.

### OTHER ADVERSE EFFECTS:

None known.

## SECTION 13. DISPOSAL CONSIDERATIONS

**Product Disposal:** Do not dispose of waste into sewer. Dispose of in accordance with local regulations.

**Packaging Disposal:** Dispose of in accordance with local regulations.

## SECTION 14. TRANSPORTATION INFORMATION

### AIR TRANSPORT (IATA):

**UN No.:** 1993  
**Proper Shipping Name:** Flammable Liquid, N.O.S. (Mineral Spirits/Isopropanol Solution)  
**Class:** 3  
**Packing group:** II  
**Labels:** Flammable Liquid

### SEA TRANSPORT (IMDG):

**UN No.:** 1993  
**Proper Shipping Name:** FLAMMABLE LIQUID, N.O.S. (MINERAL SPIRITS/ISOPROPANOL SOLUTION)  
**Class:** 3  
**Packing group:** II  
**Emergency Schedule:** F-E  
**(EmS):** S-E  
**Labels:** Flammable liquid

### ROAD / RAIL (ADR/RID) / US DOT / CANADA TDG:

**UN No.:** 1993  
**Proper Shipping Name:** Flammable Liquid, N.O.S. (Mineral Spirits/Isopropanol Solution)  
**Class:** 3  
**Packing group:** II  
**Labels:** 3

## SECTION 15. REGULATORY INFORMATION

### CHEMICAL INVENTORIES:

<b>TSCA:</b> (USA)	All ingredients are on the inventory.
<b>DSL:</b> (Canada)	All ingredients are on the inventory.
<b>EINECS:</b> (EU)	All ingredients are on or exempted from the inventory.
<b>AICS:</b> (Australia)	All ingredients are on the inventory.
<b>IECSC:</b> (China)	All ingredients are on the inventory.
<b>MITI:</b> (Japan)	All ingredients are on the inventory.
<b>KECL:</b> (Korea)	All ingredients are on the inventory.
<b>NZIoC:</b> (New Zealand)	All ingredients are on the inventory.
<b>CSNN:</b> (Taiwan)	All ingredients are on the inventory.
<b>PICCS:</b> (Philippines)	All ingredients are on the inventory.

### CANADA

This product has been classified in accordance with the hazard criteria of the CPR, and this MSDS contains all the information required by the CPR.

**WHMIS Classification: CLASS B - Division 2 | CLASS D - Division 2A | CLASS D - Division 2B**

### USA

#### **EPA SARA Title III Chemical Listings:**

Section 302 Extremely Hazardous Substances (40 CFR 355):	<b>None</b>
Section 304 CERCLA Hazardous Substances (40 CFR 302):	<b>None</b>
Section 311/312 Hazard Class (40 CFR 370):	Acute: <b>Yes</b> ; Chronic: <b>Yes</b> ; Fire: <b>Yes</b> ; Pressure: <b>No</b> ; Reactive: <b>No</b>
Section 313 Toxic Chemicals (40 CFR 372):	<b>None</b>

### Supplemental State Compliance Information

#### **California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: **None known.**

#### **Massachusetts / New Jersey / Pennsylvania**

Stoddard Solvent (CAS# 8052-41-3) 30 ó 40%

HMIS	
<b>H</b>	2
<b>F</b>	3
<b>R</b>	0



### EEC

#### **Labelling according to EEC Directive**

S-phrases: S51 (Use only in well-ventilated areas)

R-phrases: **R11: Highly Flammable / R36: Irritating to eyes / R45: May cause cancer / R46: May cause heritable genetic defects /**

**R65: Harmful- may cause lung damage if swallowed**

## SECTION 16. OTHER INFORMATION

The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. This data is offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

**SDS prepared by:** Raj Moonsammy  
**Address:** Siltech Corp  
225 Wicksteed Avenue  
Toronto, Ontario, Canada M4H 1G5  
**Telephone:** (416) 424-4567  
  
**First Issuing Date:** March 25, 2011  
**Revision No.:** 3  
**Latest Revision Date:** January 08, 2014

*This is the last page.*