

TECHNICAL DATA SHEET

Silmer[®] ACR Di-1010 TF

Silicone Acrylate Pre-polymer

DESCRIPTION

Silmer® ACR Di-1010 TF is a 100% active water dispersible di-functional silicone acrylate pre-polymer. It is used to modify acrylate and other free-radical cured polymers to improve surface and physical properties.

TYPICAL PROPERTIES

Appearance	Clear to hazy liquid
Viscosity at 25°C, cps	300
Active Content %	100
Specific Gravity @ 25°C	1.04
Water solubility @ 1% and 10%	Dispersible
Diluents	Water, aliphatic and aromatic solvents
Molecular Weight	2,000
Equivalent Weight	1,000

APPLICATION & USES

Silmer ACR Di-1010 TF can be co-reacted into acrylate polymers for coatings, plastics, resins and other applications to incorporate a silicone moiety into the polymer structure. When coreacted during the polymerization stage, **Silmer ACR Di-1010 TF** improves the surface and physical properties of the polymers. These benefits include better slip, anti-blocking, mar resistance, surface smoothness and flexibility.

The acrylate functionality in **Silmer ACR Di-1010 TF** gives a permanent binding into the matrix of the polymers which prevents the silicone from migrating to the surface. These same benefits can also be incorporated into UV cured systems or other free-radically cured systems such as polyolefins or acrylic emulsions.

For polymer modification, the typical recommended amount of **Silmer ACR Di-1010 TF** ranges from 2-20%. As an additive in UV curing system, the recommended amount ranges from 0.1-2.0%.

SHELF LIFE

When stored in the original, unopened containers between 10 and 40°C, **Silmer ACR Di-1010 TF** has a shelf life of 24 months from date of manufacture.

PACKAGING

Silmer ACR Di-1010 TF is supplied in 20kg pails and 200kg drums.

LEGAL DISCLAIMER

Siltech Corporation believes that the information in this technical data sheet is an accurate description of the typical uses of the product. Siltech Corporation, however, disclaims any liability for incidental or consequential damages, which may result from the use of the product that are beyond its control. Therefore, it is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Nothing contained herein is to be considered as permission or a recommendation to infringe any patent or any other intellectual property right.

SILMER[®] is a registered trademark of Siltech Corporation, Toronto, Ontario, Canada.