

SAFETY DATA SHEET

WHMIS 2015 • OSHA HCS (29 CFR 1910.1200) • NOM-018-STPS-2015

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name Siltech C-174
Product code 2860.2
Chemical Name Mixture

CAS No. 68937-55-3 / 1330-20-7 / 78-83-1 / 100-41-4

1.2 Recommended use of the chemical and

restrictions on use

Identified use(s) Coatings, intermediate use

Uses advised against None known

1.3 Details of the supplier of the Safety Data Sheet

Company Identification Siltech Corp

225 Wicksteed Ave

Toronto, ON Canada M4H 1G5

Telephone +1-416-424-4567 Fax +1-416-424-3158

E-Mail (competent person) marsha.carter@siltech.com

Additional Location Siltech Corp

3265 Wolfedale Road,

Mississauga ON Canada L5C 1V8

Telephone +1-905-270-5534 Fax +1-905-270-5816

1.4 Emergency telephone number

Emergency Phone No. CANUTEC - TELEPHONE: EMERGENCY USE ONLY

+1-613-996-6666

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Flam. Liq. 3

Acute Tox. 4 – Dermal Acute Tox. 4 - Inhalation

Skin Irrit. 2 Eye Dam. 1

STOT RE 2 - Hearing deterioration

2.2 Label elements

Product Name

Symbol

Siltech C-174



Signal word(s)

Hazard statement(s)

H226: Flammable liquid and vapour.
H312: Harmful in contact with skin.

H315: Causes skin irritation. H318: Causes serious eye damage.

H332: Harmful if inhaled.

 $\hbox{H373: May cause damage to organs through prolonged or}\\$

repeated exposure.

Precautionary statement(s) P210: Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof

electrical/ventilating/lighting/equipment. P242: Use only non-sparking tools.

Product: Siltech C-174 SDS #: 2860.2

> P243: Take precautionary measures against static discharge.

P260: Do not breathe dust/fume/gas/mist/vapours/spray. P264: Wash hands and exposed skin thoroughly after

P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331: Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P304+P312: IF INHALED: Call a POISON CENTER or

doctor/physician if you feel unwell.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P363: Wash contaminated clothing before reuse. P403+P235: Store in a well-ventilated place. Keep cool. P501: Dispose of contents/container to: Observe Local Regulations.

2.3 Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Mixtures

| | | | | | Hazard pictogram(s) and | |
|-------------------------|-----------------|---------|-----------|-----------|-------------------------|--|
| Hazardous ingredient(s) | Synonym(s) | %W/W | CAS No. | EC No. | Hazard statement(s) | |
| Xvlene | Dimethylbenzene | 25 - 45 | 1330-20-7 | 215-535-7 | GHS02, GHS07 | |
| Aylerie | | | | | H226, H312, H315, H332 | |
| 2-methylpropan-1-ol | iso-butanol | 5 - 15 | 78-83-1 | 201-148-0 | GHS02, GHS05, GHS07 | |
| | | | | | H226, H315, H318, H335, | |
| | | | | | H336 | |
| Ethylbenzene | EB | 4 - 8 | 100-41-4 | 202-849-4 | GHS02, GHS08, GHS07 | |
| Luiyiberizerie | LD | | | | H225, H332, H304, H373 | |

None known

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

Skin Contact

Eye Contact

Ingestion

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If symptoms persist, obtain medical attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If irritation develops and persists, get medical attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation develops and persists, get medical attention. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Get

medical attention immediately.

Product: Siltech C-174 SDS #: 2860.2

4.2 Most important symptoms and effects, both

acute and delayed

Causes skin irritation. May cause irritation to the respiratory system. Hearing deterioration.

4.3 Indication of any immediate medical attention and special treatment needed No information available.

5. SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

Suitable Extinguishing Media In case of fire, use water spray, foam, dry powder or CO2

for extinction. Keep containers cool by spraying with water if

exposed to fire.

Unsuitable Extinguishing Media

Do not use water jet.

5.2 Special hazards arising from the substance or

mixture

No information available.

5.3 Advice for fire-fighters A self contained breathing apparatus and suitable protective

clothing should be worn in fire conditions.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and Avoid contact with skin, eyes or clothing. Use personal

protective equipment as required.

emergency procedures
6.2 Environmental precautions

Reference to other sections

6.3 Methods and material for containment and

cleaning up

6.4

7.3

Avoid release to the environment.

Caution - spillages may be slippery. Cover spills with inert

absorbent material. Transfer to a container for disposal. See Section: 7 & 8.

7. SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling Avoid contact with skin and eyes. Avoid ingestion. Use

and light.

only with sufficient ventilation. Ground/bond container and receiving equipment. Wash thoroughly after handling. General hygiene measures for the handling of chemicals are applicable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a tightly closed container. Keep away from heat

7.2 Conditions for safe storage, including any

incompatibilities Storage Temperature

Storage Temperature Ambient
Storage Life Stable under normal conditions.

Incompatible materials

Specific end use(s)

Oxidizing agents
Industrial use

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

| | | LTEL (8 hr TWA | LTEL (8 hr TWA | STEL | STEL | |
|--------------|-----------|----------------|----------------|-------|---------|------|
| SUBSTANCE | CAS No. | ppm) | mg/m³) | (ppm) | (mg/m³) | Note |
| Xylene | 1330-20-7 | 100 | 435 | 150 | | |
| Ethylbenzene | 100-41-4 | 100 | 435 | | | |
| Isobutanol | 78-83-1 | 50 | | 100 | 300 | |

8.1.2 Biological limit value Not established

8.1.3 PNECs and DNELs Not established

8.2 Exposure controls

8.2.1 Appropriate engineering controls Provide adequate ventilation when using the material and

follow the principles of good occupational hygiene to control

personal exposures.

8.2.2 Personal protection equipment

Revision: 3 Page: 3/7 Date: 11/05/2023

Product: Siltech C-174 SDS #: 2860.2

Eye/face protection Eye protection with side protection (EN 166)



Skin protection (Hand protection/ Other) Wear impervious gloves (EN374). Nitrile rubber, Polyethylene, PVC

Wear suitable protective clothing.

Wear suitable respiratory protective equipment if processing Respiratory protection

involves working in areas where dusts or vapours are likely

to be evolved.

Thermal hazards Flammable liquid

8.2.3 Environmental Exposure Controls Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical

properties

Appearance Colourless to yellowish liquid.

Odour Characteristic odour.

Odour Threshold Not available. рΗ Not available. Melting Point/Freezing Point Not available. Initial boiling point and boiling range Not available.

Flash point (PMCC) 30°C

Evaporation rate Not available. Not applicable. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Vapour pressure Not available. Not available. Vapour density

Relative density / Specific Gravity (20°C) 0.94

Solubility(ies) Insoluble in water. Partition coefficient: n-octanol/water Not available. Not available. Auto-ignition temperature **Decomposition Temperature** Not available. Viscosity (25°C) 10 - 50 cpsNot applicable. Explosive properties Not applicable. Oxidising properties

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity Stable under normal conditions. 10.2 **Chemical stability** Stable under normal conditions.

10.3 Possibility of hazardous reactions Will not occur

10.4 Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

10.5 Incompatible materials Oxidizing agents, Acids, Alkaline **Hazardous Decomposition Product(s)** Carbon oxides may be formed.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Ingestion Harmful if swallowed. Inhalation Harmful by inhalation. Skin Contact Causes skin irritation. Eye Contact Causes serious eye damage.

Effects and Symptoms

Revision: 3 Date: 11/05/2023 Page: 4/7

Product: Siltech C-174 SDS #: 2860.2

skin corrosion/irritation Causes skin irritation. Causes serious eye damage. Serious eye damage/irritation

Respiratory or skin sensitization Not classified Germ cell mutagenicity Not classified Carcinogenicity Not classified Reproductive toxicity Not classified

STOT - single exposure The vapour may have narcotic effect.

STOT - repeated exposure Repeated and/or prolonged contact may cause: Hearing

deterioration

Aspiration hazard Not classified Delayed and chronic effects Not available Calculated acute toxicity estimate (ATE) Not available

12. SECTION 12: ECOLOGICAL INFORMATION

| 12.1 | Toxicity | Not available. |
|------|------------------------------------|----------------|
| 12.2 | Persistence and degradability | Not available. |
| 12.3 | Bioaccumulative potential | Not available. |
| 12.4 | Mobility in soil | Not available. |
| 12.5 | Results of PBT and VPVB assessment | Not available. |
| 12.6 | Other adverse effects | None known |

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods Do not empty into drains; dispose of this material and its

container in a safe way.

13.2 **Additional Information** Dispose of contents in accordance with local, state or

national legislation.

14. SECTION 14: TRANSPORT INFORMATION

14.1 **UN** number

FLAMMABLE LIQUIDS N.O.S. (Xylene Solution) 14.2 UN proper shipping name

14.3 Class 3 Packing group III

15. SECTION 15: REGULATORY INFORMATION

15.1 **EU** regulations

Polymer exempt / Not available REACH Registration No.

Candidate List of Substances of Very High

Possible trace amounts of:

Concern for Authorisation Octamethylcyclotetrasiloxane (CAS# 556-67-2) < 0.01%

Decamethylcyclopentasiloxane (CAS# 541-02-6) < 0.1% Dodecamethylcyclohexasiloxane (CAS# 540-97-6) < 0.1%

1,4-Dioxane (CAS# 123-91-1) < 1 ppm

15.2 International Inventories

| | | Not | Polymer | |
|--------------------------------|----------|--------|---------|-------|
| Country | Listed | listed | exempt | Other |
| United States (TSCA) | Active√ | | | |
| Canada (DSL/NDSL) | DSL√ | | | |
| European Union (EINECS/ELINCS) | ✓ | | ✓ | |
| Australia (AICS) | ✓ | | | |
| China (IECSC) | ✓ | | | |
| Japan (ENCS) | ✓ | | | |
| South Korea (KECI) | √ | | | |
| Taiwan (TCSI) | √ | | | |
| New Zealand (NZIoC) | √ | | | |
| Philippines (PICCS) | ✓ | | | |

Product: Siltech C-174 SDS #: 2860.2

15.3 National regulations

United States (TSCA) TSCA Inventory Status : All chemicals in this product comply

with TSCA rules and regulations including TSCA Section 5

(Inventory Rules).

HMIS (Hazardous Material Information System)

NFPA Rating

H = 2 / F = 3 / R = 0 H = 2 / F = 3 / R = 0

15.4 US State Regulations

15.4.1 SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR

OTHER REPRODUCTIVE HARM

Specific Listing(s) not required Possible trace amounts of:

Ethylene Oxide (CAS# 75-21-8) < 1 ppm

15.4.2 SUBSTANCES KNOWN TO THE STATE OF

CALIFORNIA TO CAUSE CANCER

Ethylbenzene (CAS# 100-41-4) 4 - 8%

Specific Listing(s) not required Possible trace amounts of:

Ethylene Oxide (CAS# 75-21-8) < 1 ppm 1,4-Dioxane (CAS# 123-91-1) < 1 ppm

15.4.3 State Right to Know Lists

Xylene (CAS# 1330-20-7) 25 - 45% Isobutanol (CAS# 78-83-1) 5 - 15% Ethylbenzene (CAS# 100-41-4) 4 - 8%

Specific Listing(s) not required Possible trace amounts of:

Octamethylcyclotetrasiloxane (CAS# 556-67-2) < 0.01%

Ethylene Oxide (CAS# 75-21-8) < 1 ppm 1,4-Dioxane (CAS# 123-91-1) < 1 ppm

16. SECTION 16: OTHER INFORMATION

Revision: May 11, 2023

LEGEND

LTEL Long Term Exposure Limit

STEL Short Term Exposure Limit

STOT Specific Target Organ Toxicity

DNEL Derived No Effect Level

PNEC Predicted No Effect Concentration
PBT Persistent, Bioaccumulative and Toxic
vPvB very Persistent and very Bioaccumulative

Hazard statement(s) and Precautionary statement(s)

H226: Flammable liquid and vapour.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H332: Harmful if inhaled.

H373: May cause damage to organs through prolonged or repeated exposure:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240: Ground/bond container and receiving equipment.

 $P241: Use\ explosion-proof\ electrical/ventilating/lighting/equipment.$

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331: Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Revision: 3 Page: 6/7 Date: 11/05/2023

Product: Siltech C-174 SDS #: 2860.2

P332+P313: If skin irritation occurs: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P363: Wash contaminated clothing before reuse.

P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/container to: Observe Local Regulations.

Hazard pictogram(s) and Hazard Symbol



Additional Information

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Siltech Corp. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Siltech Corp. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Revision: 3 Page: 7/7 Date: 11/05/2023