

# **SAFETY DATA SHEET**

WHMIS 2015 • OSHA HCS (29 CFR 1910.1200) • NOM-018-STPS-2015

# 1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name Silmer VQ9 XYL

Product code 5598.009

Chemical Name Silica, [(ethenyldimethylsilyl)oxy]- and [(trimethylsilyl)oxy]-

modified

CAS No. 68988-89-6 / 1330-20-7 / 100-41-4

1.2 Recommended use of the chemical and

restrictions on use

Identified use(s) intermediate use, Additive

Uses advised against None known

1.3 Details of the supplier of the Safety Data Sheet

Company Identification Siltech Corp

225 Wicksteed Ave

Toronto, ON Canada M4H 1G5

Telephone +1-416-424-4567 Fax +1-416-424-3158

E-Mail (competent person) marsha.carter@siltech.com

Additional Location Siltech Corp

3265 Wolfedale Road,

Mississauga ON Canada L5C 1V8

Telephone +1-905-270-5534 Fax +1-905-270-5816

1.4 Emergency telephone number

Emergency Phone No. CANUTEC - TELEPHONE: EMERGENCY USE ONLY

+1-613-996-6666

# 2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Flam. Liq. 3

Acute Tox. 4 – Dermal Acute Tox. 4 - Inhalation

Skin Irrit. 2

STOT RE 2 - Hearing deterioration

Asp. Tox. 1

2.2 Label elements

Product Name Silmer VQ9 XYL

Symbol



Signal word(s) DANGER

Hazard statement(s) H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin. H315: Causes skin irritation. H332: Harmful if inhaled.

H373: May cause damage to organs through prolonged or

repeated exposure.

Precautionary statement(s) P210: Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof

electrical/ventilating/lighting/equipment.

Product: Silmer VQ9 XYL SDS #: 5598.009

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust/fume/gas/mist/vapours/spray. P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331: Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

P363: Wash contaminated clothing before reuse. P403+P235: Store in a well-ventilated place. Keep cool. P501: Dispose of contents/container to: Observe Local Regulations.

2.3 Other hazards

# 3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Mixtures

					Hazard pictogram(s) and	
Hazardous ingredient(s)	Synonym(s)	%W/W	CAS No.	EC No.	Hazard statement(s)	
Xylene	Dimethylbenzene	25 - 35	1330-20-7	215-535-7	GHS02, GHS07	
					H226, H312, H315, H332	
Ethylbenzene	EB	5 - 10	100-41-4	202-849-4	GHS02, GHS08, GHS07	
Luiyiberizerie					H225, H332, H304, H373	

None known

#### 4. SECTION 4: FIRST AID MEASURES



# 4.1 Description of first aid measures

Inhalation

Skin Contact

Eye Contact

Ingestion

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If symptoms persist, obtain medical attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If irritation develops and persists, get medical attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation develops and persists, get medical attention. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Get medical attention immediately.

Causes skin irritation. May cause irritation to the respiratory system. Hearing deterioration.

No information available.

Revision: 3 Page: 2/7 Date: 03/10/2023

Product: Silmer VQ9 XYL SDS #: 5598.009

# 5. SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

Suitable Extinguishing Media In case of fire, use water spray, foam, dry powder or CO2

for extinction. Keep containers cool by spraying with water if

exposed to fire.

Unsuitable Extinguishing Media Do not use water jet.

5.2 Special hazards arising from the substance or

mixture

Silicon Dioxide, carbon oxides, incompletely burned carbon

compounds, formaldehyde.

5.3 Advice for fire-fighters A self contained breathing apparatus and suitable protective

clothing should be worn in fire conditions.

# 6. SECTION 6: ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and** Avoid contact with skin, eyes or clothing. Use personal **emergency procedures** protective equipment as required.

**6.2 Environmental precautions**Avoid release to the environment.

6.3 Methods and material for containment and cleaning up Caution - spillages may be slippery. Cover spills with inert absorbent material. Transfer to a container for disposal.

**6.4 Reference to other sections** See Section: 7 & 8.

# 7. SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling Avoid contact with skin and eyes. Avoid ingestion. Use

only with sufficient ventilation. Wash thoroughly after handling. General hygiene measures for the handling of chemicals are applicable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

Store in a tightly closed container. Keep away from heat

No smoking.

and light.

7.2 Conditions for safe storage, including any

incompatibilities

Amhient

Storage Temperature Ambient

Storage Life Stable under normal conditions.

Incompatible materials

Oxidizing agents

7.3 Specific end use(s) Industrial use

# 8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters

# 8.1.1 Occupational Exposure Limits

		LTEL (8 hr TWA	LTEL (8 hr TWA	STEL	STEL	
SUBSTANCE	CAS No.	ppm)	mg/m³)	(ppm)	(mg/m³)	Note
Xylene	1330-20-7	100	435	150		
Ethylbenzene	100-41-4	100	435			

8.1.2 Biological limit value Not established

8.1.3 PNECs and DNELs Not established

8.2 Exposure controls

**8.2.1 Appropriate engineering controls** Provide adequate ventilation when using the material and

follow the principles of good occupational hygiene to control

personal exposures.

8.2.2 Personal protection equipment

Eye/face protection Eye protection with side protection (EN 166)



Skin protection (Hand protection/ Other) Wear impervious gloves (EN374).

Nitrile rubber, Polyethylene, PVC

Product: Silmer VQ9 XYL SDS #: 5598.009



Wear suitable protective clothing.

Respiratory protection



Wear suitable respiratory protective equipment if processing involves working in areas where dusts or vapours are likely

to be evolved.

Thermal hazards None.

**8.2.3 Environmental Exposure Controls** Avoid release to the environment.

# 9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical

properties

Appearance Colourless to yellowish liquid.

Odour
Odour Characteristic odour.
Odour Threshold
PH
Not available.
Melting Point/Freezing Point
Not available.
Initial boiling point and boiling range
Flash point (PMCC)
Characteristic odour.
Not available.
Not available.
34°C

Evaporation rate

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Vapour pressure

Vapour density

Relative density / Specific Gravity (20°C)

Solubility(ies)

Partition coefficient: n-octanol/water

Auto-ignition temperature

Not available.

Not available.

Not available.

Not available.

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition Temperature

Viscosity (25°C)

Explosive properties

Not available.

Not available.

Not available.

Not available.

Not applicable

Explosive properties Not applicable. Oxidising properties Not applicable.

# 10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity Stable under normal conditions.
 10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Will not occur

10.4 Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

10.5 Incompatible materials
 10.6 Hazardous Decomposition Product(s)
 Oxidizing agents, Acids, Alkaline
 Carbon oxides may be formed.

# 11. SECTION 11: TOXICOLOGICAL INFORMATION

# 1.1 Information on toxicological effects

**Acute toxicity** 

IngestionHarmful if swallowed.InhalationHarmful by inhalation.Skin ContactCauses skin irritation.Eye ContactMay cause eye irritation.

Effects and Symptoms

 skin corrosion/irritation
 Causes skin irritation.

 Serious eye damage/irritation
 May cause eye irritation.

 Respiratory or skin sensitization
 May cause respiratory irritation.

Germ cell mutagenicity Not classified

Revision: 3 Page: 4/7 Date: 03/10/2023

# Siltech Corp 225 Wicksteed Ave. Toronto, ON Canada M4H 1G5 1-416-424-4567 www.siltech.com

Product: Silmer VQ9 XYL SDS #: 5598.009

Carcinogenicity Not classified Reproductive toxicity Not classified STOT - single exposure Not classified

STOT - repeated exposure Repeated and/or prolonged contact may cause: Hearing

> deterioration Not classified

Aspiration hazard Not available Delayed and chronic effects Calculated acute toxicity estimate (ATE) Not available

#### 12. SECTION 12: ECOLOGICAL INFORMATION

12.1 **Toxicity** Not available. Persistence and degradability Not available. 12.2 Bioaccumulative potential Not available. 12.3 Mobility in soil Not available. 12.4 Results of PBT and VPVB assessment Not available. 12.5 Other adverse effects None known

#### 13. SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods Do not empty into drains; dispose of this material and its

container in a safe way.

13.2 **Additional Information** Dispose of contents in accordance with local, state or

national legislation.

# 14. SECTION 14: TRANSPORT INFORMATION

14.1 1993 UN number

FLAMMABLE LIQUIDS N.O.S. (Xylene Solution) 14.2 UN proper shipping name

14.3 Class 3 Packing group III

# 15. SECTION 15: REGULATORY INFORMATION

#### 15.1 **EU regulations**

REACH Registration No. Polymer exempt / Not available

Candidate List of Substances of Very High Concern None known.

for Authorisation

#### 15.2 **International Inventories**

		Not	Polymer	
Country	Listed	listed	exempt	Other
United States (TSCA)	Active√			
Canada (DSL/NDSL)	DSL√			
European Union (EINECS/ELINCS)	✓		✓	
Australia (AICS)	✓			
China (IECSC)	✓			
Japan (ENCS)	<b>√</b>			
South Korea (KECI)	<b>√</b>			
Taiwan (TCSI)	✓			
New Zealand (NZIoC)	✓			
Philippines (PICCS)	✓			

#### 15.3 **National regulations**

United States (TSCA)

TSCA Inventory Status: All chemicals in this product comply with TSCA rules and regulations including TSCA Section 5

(Inventory Rules).

#### Siltech Corp 225 Wicksteed Ave. Toronto, ON Canada M4H 1G5 1-416-424-4567 www.siltech.com

Product: Silmer VQ9 XYL SDS #: 5598.009

HMIS (Hazardous Material Information System) H = 2/F = 3/R = 0NFPA Rating H = 2/F = 3/R = 0

15.4 US State Regulations

**15.4.1** SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM

15.4.2 SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER

15.4.3 State Right to Know Lists

None known.

Ethylbenzene (CAS# 100-41-4) 5 - 10%

Xylene (CAS# 1330-20-7) 25 - 35% Ethylbenzene (CAS# 100-41-4) 5 - 10%

# 16. SECTION 16: OTHER INFORMATION

Revision: October 03, 2023

#### **LEGEND**

LTEL Long Term Exposure Limit
STEL Short Term Exposure Limit
STOT Specific Target Organ Toxicity
DNEL Derived No Effect Level

PNEC Predicted No Effect Concentration
PBT Persistent, Bioaccumulative and Toxic
PVPB Persistent and very Bioaccumulative

#### Hazard statement(s) and Precautionary statement(s)

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H373: May cause damage to organs through prolonged or repeated exposure:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331: Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

P363: Wash contaminated clothing before reuse.

P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/container to: Observe Local Regulations.

# Hazard pictogram(s) and Hazard Symbol



Revision: 3 Page: 6/7 Date: 03/10/2023

# Siltech Corp 225 Wicksteed Ave. Toronto, ON Canada M4H 1G5 1-416-424-4567 www.siltech.com

Product: Silmer VQ9 XYL SDS #: 5598.009

#### Additional Information

#### **Disclaimers**

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Siltech Corp. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Siltech Corp. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Revision: 3 Page: 7/7 Date: 03/10/2023