

SAFETY DATA SHEET

WHMIS 2015 • OSHA HCS (29 CFR 1910.1200) • NOM-018-STPS-2015

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name Product code Chemical Name CAS No.

- 1.2 Recommended use of the chemical and restrictions on use Identified use(s) Uses advised against
- **1.3 Details of the supplier of the Safety Data Sheet** Company Identification

Telephone Fax E-Mail (competent person)

Additional Location

Telephone Fax

1.4 Emergency telephone number Emergency Phone No.

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

2.2 Label elements Product Name Symbol

> Signal word(s) Hazard statement(s)

Precautionary statement(s)

Silmer Q9 XYL

7050.709 Mixture 68988-56-7 / 1330-20-7 / 100-41-4

intermediate use, Additive None known

Siltech Corp 225 Wicksteed Ave Toronto, ON Canada M4H 1G5 +1-416-424-4567 +1-416-424-3158 marsha.carter@siltech.com

Siltech Corp 3265 Wolfedale Road, Mississauga ON Canada L5C 1V8 +1-905-270-5534 +1-905-270-5816

CANUTEC - TELEPHONE: EMERGENCY USE ONLY +1-613-996-6666

Flam. Liq. 3 Acute Tox. 4 – Dermal Acute Tox. 4 - Inhalation Skin Irrit. 2 STOT RE 2 - Hearing deterioration Asp. Tox. 1

Silmer Q9 XYL



DANGER

H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H332: Harmful if inhaled.
H373: May cause damage to organs through prolonged or repeated exposure.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting/equipment.
P242: Use only non-sparking tools.

Produ	act: Silmer Q9 XYL	1-416-424-4567	www.siltech.com SDS #: 7050.709
2.3	Other hazards		 P243: Take precautionary measures against static discharge. P260: Do not breathe dust/fume/gas/mist/vapours/spray. P264: Wash hands and exposed skin thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331: Do NOT induce vomiting. P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P332+P313: If skin irritation occurs: Get medical advice/attention. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell. P363: Wash contaminated clothing before reuse. P403+P235: Store in a well-ventilated place. Keep cool. P501: Dispose of contents/container to: Observe Local Regulations. None known

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Mixtures

Hazardous ingredient(s)	Synonym(s)	%W/W	CAS No.	EC No.	Hazard pictogram(s) and Hazard statement(s)
Xylene	Dimethylbenzene	25 - 35	1330-20-7	215-535-7	GHS02, GHS07 H226, H312, H315, H332
Ethylbenzene	EB	5 - 10	100-41-4	202-849-4	GHS02, GHS08, GHS07 H225, H332, H304, H373

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If symptoms persist, obtain medical attention. Skin Contact IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If irritation develops and persists, get medical attention. Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation develops and persists, get medical attention. Ingestion IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Get medical attention immediately. Most important symptoms and effects, both Causes skin irritation. May cause irritation to the respiratory system. Hearing deterioration. acute and delayed Indication of any immediate medical No information available. attention and special treatment needed

4.2

4.3

5.1 **Extinguishing Media** Suitable Extinguishing Media In case of fire, use water spray, foam, dry powder or CO2 for extinction. Keep containers cool by spraying with water if exposed to fire. Do not use water jet. Unsuitable Extinguishing Media 5.2 Special hazards arising from the substance or Silicon Dioxide, carbon oxides, incompletely burned carbon mixture compounds, formaldehyde. 5.3 Advice for fire-fighters A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. SECTION 6: ACCIDENTAL RELEASE MEASURES

0.	SECTION 0. ACCIDENTAL RELEASE WEA	JORES
6.1	Personal precautions, protective equipment and	Avoid contact with skin, ev

6.1	Personal precautions, protective equipment and emergency procedures	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.
6.2	Environmental precautions	Avoid release to the environment.
6.3	Methods and material for containment and	Caution - spillages may be slippery. Cover spills with inert
	cleaning up	absorbent material. Transfer to a container for disposal.
6.4	Reference to other sections	See Section: 7 & 8.

SECTION 7: HANDLING AND STORAGE 7.

5. SECTION 5: FIRE-FIGHTING MEASURES

Procentions for safe bandling 7.1

Precautions for safe handling	Avoid contact with skin and eyes. Avoid ingestion. Use only with sufficient ventilation. Ground/bond container and receiving equipment. Wash thoroughly after handling. General hygiene measures for the handling of chemicals are applicable.
Conditions for safe storage, including any incompatibilities	Store in a tightly closed container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Storage Temperature	Ambient
Storage Life	Stable under normal conditions.
Incompatible materials	Oxidizing agents
Specific end use(s)	Industrial use

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION 8.

Control parameters 8.1

7.2

7.3

8.1.1 **Occupational Exposure Limits**

		LTEL (8 hr TWA	LTEL (8 hr TWA	STEL	STEL	
SUBSTANCE	CAS No.	ppm)	mg/m³)	(ppm)	(mg/m³)	Note
Xylene	1330-20-7	100	435	150		
Ethylbenzene	100-41-4	100	435			

8.1.2	Biological	limit	value
-------	------------	-------	-------

- 8.1.3 PNECs and DNELs
- 8.2 **Exposure controls**
- 8.2.1 Appropriate engineering controls
- 8.2.2 Personal protection equipment Eye/face protection



Not established

Not established

Provide adequate ventilation when using the material and follow the principles of good occupational hygiene to control personal exposures.

Eye protection with side protection (EN 166)

SDS #: 7050.709

Skin protection (Hand protection/ Other)



Respiratory protection



Thermal hazards

8.2.3 Environmental Exposure Controls

Wear impervious gloves (EN374). Nitrile rubber, Polyethylene, PVC Wear suitable protective clothing.

Wear suitable respiratory protective equipment if processing involves working in areas where dusts or vapours are likely to be evolved.

Flammable liquid Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical

properties	
Appearance	Colourless to yellowish liquid.
Odour	Characteristic odour.
Odour Threshold	Not available.
рН	Not available.
Melting Point/Freezing Point	Not available.
Initial boiling point and boiling range	Not available.
Flash point (PMCC)	34°C
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density / Specific Gravity (20°C)	1.07
Solubility(ies)	Insoluble in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity (25°C)	10 - 40 cps
Explosive properties	Not applicable.
Oxidising properties	Not applicable.

10. SECTION 10: STABILITY AND REACTIVITY

- 10.1 Reactivity
- 10.2 Chemical stability
- 10.3 Possibility of hazardous reactions
- 10.4 Conditions to avoid
- 10.5 Incompatible materials
- 10.6 Hazardous Decomposition Product(s)

11. SECTION 11: TOXICOLOGICAL INFORMATION

- 11.1 Information on toxicological effects Acute toxicity
 - Ingestion Inhalation Skin Contact Eye Contact

Effects and Symptoms skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Oxidizing agents, Acids, Alkaline Carbon oxides may be formed.

Harmful if swallowed. Harmful by inhalation. Causes skin irritation. May cause eye irritation.

Stable under normal conditions.

Stable under normal conditions.

Will not occur

Causes skin irritation. May cause eye irritation. May cause respiratory irritation. Not classified

SDS #: 7050.709

Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT - single exposure	Not classified
STOT - repeated exposure	Repeated and/or prolonged contact may cause: Hearing
	deterioration
Aspiration hazard	Aspiration hazard - Category 1
Delayed and chronic effects	Not available
Calculated acute toxicity estimate (ATE)	Not available

Not available.

Not available.

Not available.

Not available.

Not available.

None known

12. SECTION 12: ECOLOGICAL INFORMATION

12.1	Toxicity
------	----------

- 12.2 Persistence and degradability
- 12.3 Bioaccumulative potential
- 12.4 Mobility in soil

Product: Silmer Q9 XYL

- 12.5 Results of PBT and VPVB assessment
- 12.6 Other adverse effects

13. SECTION 13: DISPOSAL CONSIDERATIONS

- 13.1 Waste treatment methods
- 13.2 Additional Information

Do not empty into drains; dispose of this material and its container in a safe way. Dispose of contents in accordance with local, state or national legislation.

14. SECTION 14: TRANSPORT INFORMATION

- 14.1 UN number
- **14.2** UN proper shipping name
- 14.3 Class

1993 FLAMMABLE LIQUIDS N.O.S. (Xylene Solution) 3 Packing group III

15. SECTION 15: REGULATORY INFORMATION

15.1 EU regulations REACH Registration No.

Not available

Candidate List of Substances of Very High Concern None known. for Authorisation

15.2 International Inventories

		Not	Polymer	
Country	Listed	listed	exempt	Other
United States (TSCA)	Active√			
Canada (DSL/NDSL)	DSL√			
European Union (EINECS/ELINCS)	\checkmark		\checkmark	
Australia (AICS)	\checkmark			
China (IECSC)	\checkmark			
Japan (ENCS)	\checkmark			
South Korea (KECI)	\checkmark			
Taiwan (TCSI)	\checkmark			
New Zealand (NZIoC)	\checkmark			
Philippines (PICCS)	\checkmark			

15.3	National regulations	
	United States (TSCA)	TSCA Inventory Status : All chemicals in this product comply with TSCA rules and regulations including TSCA Section 5 (Inventory Rules).
	HMIS (Hazardous Material Information System)	H = 2 / F = 3 / R = 0
	NFPA Rating	H = 2 / F = 3 / R = 0
15.4	US State Regulations	
15.4.1	SUBSTANCES KNOWN TO THE STATE OF	None known.
	CALIFORNIA TO CAUSE BIRTH DEFECTS OR	
	OTHER REPRODUCTIVE HARM	

15.4.2 SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER

15.4.3 State Right to Know Lists

Ethylbenzene (CAS# 100-41-4) 5 - 10%

Xylene (CAS# 1330-20-7) 25 - 35% Ethylbenzene (CAS# 100-41-4) 5 - 10%

16. SECTION 16: OTHER INFORMATION

Revision: July 13, 2023

LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
STOT	Specific Target Organ Toxicity
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative

Hazard statement(s) and Precautionary statement(s)

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H373: May cause damage to organs through prolonged or repeated exposure:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331: Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

P363: Wash contaminated clothing before reuse.

P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/container to: Observe Local Regulations.

Hazard pictogram(s) and Hazard Symbol



Additional Information

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Siltech Corp. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Siltech Corp. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.