



**SILTECH CORPORATION**  
225 Wicksteed Avenue  
Toronto, Ontario, Canada, M4H 1G5  
(416)424-4567 (Tel) (416)424-3158 (Fax)

TECHNICAL DATA SHEET

**Siltech® C-1910**

Fluorinated Silicone Polyether

**DESCRIPTION**

**Siltech®C-1910** is a liquid fluorinated silicone polyether. The fluoro pendant moiety gives excellent slip and foam control in UV curing systems.

**TYPICAL PROPERTIES**

Appearance	Clear to Hazy Liquid
Viscosity, cps	1500
Active Content %	100
Colour, Gardner	3 Max
Solubility (1% and 10%): -Water -IPA -Mineral Oil -Xylene, toluene	-Soluble -Soluble -Insoluble -Soluble

**USES AND APPLICATIONS**

**Siltech®C-1910** provides excellent slip and defoaming for radiation cure inks and coatings. Key product applications include:

- UV curing inks and coatings, water-based inks and coatings.

Recommended usage level is between 0.01 – 0.5 wt% of the formulation.

**SAFETY**

Before handling, read the Material Safety Data Sheet and container label for safe use, physical and health hazard information

**STORAGE AND SHELF LIFE**

When stored in the original, unopened containers between 10 and 40°C, **Siltech®C-1910** has a shelf life of 36 months from date of manufacture.

**PACKAGING**

**Siltech®C-1910** is available in 20 Kg and 200 Kg containers.

**LEGAL DISCLAIMER**

Siltech Corporation believes that the information in this technical data sheet is an accurate description of the typical uses of the product. Siltech Corporation, however, disclaims any liability for incidental or consequential damages, which may result from the use of the product that are beyond its control. Therefore, it is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Nothing contained herein is to be considered as permission or a recommendation to infringe any patent or any other intellectual property right.

**SILTECH®** is a registered trademark of Siltech Corporation, Toronto, Ontario, Canada.

Issued: January 2012