



SILTECH CORP.

Safety Data Sheet

Prepared in accordance with GHS standard
& Annex II - EC regulation 1907/2006 and amendments

Siltech C-261
SDS No: 2093

Last Revision Date: November 15, 2012

SECTION 1. IDENTIFICATION

Material Identification: Siltech C-261

Chemical Name: Polydimethylsiloxane copolymer in Butyl Acetate
Chemical Classification: Silicone

CAS #: 68937-54-2 / 123-86-4

Company Identification: Siltech Corp.

225 Wicksteed Avenue
Toronto, Ontario
Canada
M4H 1G5
(416) 424-4567

Recommended Product Usage

Coatings

CANUTEC 24-HOUR EMERGENCY RESPONSE TELEPHONE NUMBER: (613) 996-6666

USE IN CASE OF A DANGEROUS GOODS EMERGENCY

SECTION 2. HAZARD(S) IDENTIFICATION

HAZARD CLASSIFICATION:

Flammable liquid: Category 3

Specific Target Organ Toxicity (single exposure): Category 3

GHS LABEL ELEMENTS (including precautionary statements):

Symbol :



Signal Word:

Warning

Hazard Risk Statement:

H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

Precautionary Statement:

Prevention:

P210: Keep container tightly closed and away from ignition sources such as heat, sparks and open flame. NO SMOKING.

P240: Ground all equipment and use only non-sparking tools.

P280: Wear suitable protective clothing, gloves and eye protection.

Response:

P305 + P351: IF IN EYES: Rinse with water for several minutes. Repeat if needed.

P303 + P361+P353: IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Storage:

P403 + P235: Store in well-ventilated place. Keep cool.

Disposal:

P501: Dispose of contents/container in accordance with local / regional / national / international regulations.

OTHER HAZARD (risk not included in classification):

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Common Name or Synonym</u>	<u>CAS No.</u>	<u>EINECS/ELINCS No.</u>	<u>% (w/w)</u>	<u>GHS Classification</u>	<u>Classification according to Directive 67-548/EEC</u>
n-Butyl Acetate	Butyl acetate	123-86-4	204-658-1	80 - 90	Flammable liquid: Category 3 Specific Target Organ Toxicity (single exposure): Category 3	R10 R66 R67

Other ingredients not listed in this section are non-hazardous or business confidential.

SECTION 4. FIRST AID MEASURES

Eyes: Immediately flush with water. If irritation persists, obtain medical attention.

Skin: Wash off with soap and water. . If irritation persists, obtain medical attention.

Inhalation: Immediately remove to fresh air. Give oxygen for breathing difficulty. If breathing has stopped give artificial respiration. If breathing and pulse are absent give CPR. Immediately obtain medical attention. Stay with casualty until medical assistance is reached.

Ingestion: DO NOT INDUCE VOMITING. If patient is fully conscious and not convulsing, give 2 to 4 glasses of water to dilute the material. Transport to medical facility. If spontaneous vomiting occurs have victim lean forward to avoid breathing in of emesis. Rinse mouth and administer more water.

SECTION 5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Carbon dioxide, dry powder, foam, or water spray. Water can be used to cool fire exposed containers.

Unsuitable Extinguishing Media: None known.

Specific Hazards Arising from the Chemical: Silicon Dioxide. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

Special Protective Actions for Fire-Fighters: Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. Use water spray to cool fire exposed containers.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Protective Equipment: Avoid eye and skin contact. Use personal protective equipment.

Environmental Precautions: Prevent from entering drains or water sources.

Containment/Clean up: Collect for disposal. Clean up remaining materials from spill with suitable absorbent. For large spills provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean area as appropriate since some silicone material, even in small quantities, may present a slip hazard. Final cleaning may require steam, solvents or detergents.

SECTION 7. HANDLING AND STORAGE

Handling Precautions: Avoid eye and skin contact. Do not take internally. Use with adequate ventilation. Wash after handling. Exercise good industrial hygiene practice.

Storage Conditions: Keep container tightly closed and away from heat, sparks, and flame. Ground all equipment. Static electricity will accumulate and may ignite vapours.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMIT VALUES / BIOLOGICAL LIMIT VALUES:

Industrial Hygiene Standards

<u>Ingredient</u>	<u>CAS No.</u>	<u>Exposure Limit</u>
n-Butyl acetate	123-86-4	OSHA PEL: 150ppm ACGIH TLV: 150ppm (TWA)

ENGINEERING CONTROLS:

Local Ventilation: Required.
General ventilation: Required.

PERSONAL PROTECTIVE EQUIPMENT:

Respiratory protection: In the case of vapour formation use a respirator with an approved filter.
Hand protection: Chemical protective gloves should be worn for repeated or prolonged contact.
Eye protection: Safety glasses should be worn.
Skin protection: Protective equipment is not normally required.
Hygiene measures: Observe good industrial hygiene practices. Wash after handling.

Note: These precautions are for room temperature handling. Use at elevated temperatures or aerosol spray applications may require added precautions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

<u>Appearance:</u>	Clear liquid	<u>Viscosity @25°C:</u>	3 cps
<u>Colour:</u>	Colourless	<u>Melting/Freezing Point:</u>	Not determined
<u>Odour:</u>	Characteristic	<u>Initial Boiling Point:</u>	>100°C @ 760 mmHg
<u>Odour Threshold:</u>	Not determined	<u>Boiling Range:</u>	Not determined
<u>Flash Point:</u>	27°C (Pensky-Martens closed cup)	<u>Explosive Properties:</u>	No
<u>Flammability:</u>	Not determined	<u>Vapour Pressure @25°C:</u>	Not determined
<u>Flammability Limits:</u>	Not determined	<u>Vapour Density:</u>	Not determined
<u>Auto-ignition Temperature:</u>	421°C	<u>Partition Coefficient:</u>	Not determined
<u>Decomposition Temperature:</u>	Not determined	<u>pH:</u>	Not determined
<u>Specific Gravity @25°C:</u>	0.91	<u>Oxidising Properties:</u>	No
<u>Solubility in Water:</u>	Not determined	<u>Evaporation Rate:</u>	Not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Heat, flames, and sources of ignition.

Incompatible Materials: Alkali metals, strong mineral acids, oxidizing agents and halogens.

Hazardous Decomposition Products: The following decomposition products may form during fire or at very high temperatures: Carbon Oxides, Silicon dioxide, Formaldehyde, and traces of incompletely burned carbon compounds.

SECTION 11. TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EXPOSURE:

Respiratory:	Exposure is expected.
Oral:	Exposure is expected.
Eye, Skin:	Exposure is expected.

INFORMATION ON THE HEALTH HAZARDS:

Acute Toxicity:

Eyes:	Direct contact may cause temporary redness and discomfort.
Skin:	n-Butyl Acetate: (LD50 dermal: rabbit 17600 mg/kg)
Inhalation:	No significant irritation expected from a single short-term exposure.
Ingestion:	n-Butyl Acetate: (LD50 oral: rat 10800 mg/kg)

Chronic Toxicity:

Skin:	No known applicable information.
Inhalation:	No known applicable information.
Ingestion:	Repeated ingestion or swallowing large amounts may injure internally.
Other Health Hazard	No known applicable information.

Skin Corrosion/Irritation: No known applicable information.

Serious Eye Damage/Irritation: No known applicable information.

Respiratory Sensitization: No known applicable information.

Skin Sensitization: No known applicable information.

Carcinogenicity: No known applicable information.

Germ Cell Mutagenicity: No known applicable information.

Reproductive Toxicity: No known applicable information.

Specific Target Organ: May cause respiratory irritation. May cause drowsiness or dizziness.

(Systemic Toxicity – Single exposure)

Specific Target Organ: No known applicable information.

(Systemic Toxicity – Repeated exposure)

Aspiration Hazard: No known applicable information.

SECTION 12. ECOLOGICAL INFORMATION

ECOTOXICITY:

Environmental Effects

Acute: n-Butyl Acetate: Fish LC50 – 81mg/l - 96h

Chronic: None known.

PERSISTENCE AND DEGRADABILITY:

Degradation: In soil, siloxanes are degraded. The organic solvent is biodegradable.

Environmental Fate and Distribution: Siloxanes are removed from water by sedimentation sewage or binding to sludge. Organic solvents may evaporate into atmosphere and degrade.

BIOACCUMULATIVE POTENTIAL:

Bioaccumulation: No bioaccumulation potential.

MOBILITY IN SOIL:

None known.

OTHER ADVERSE EFFECTS:

None known.

SECTION 13. DISPOSAL CONSIDERATIONS

Product Disposal: Do not dispose of waste into sewer. Dispose of in accordance with local regulations.

Packaging Disposal: Dispose of in accordance with local regulations.

SECTION 14. TRANSPORTATION INFORMATION

AIR TRANSPORT (IATA):

UN No.: 1123
Proper Shipping Name: Butyl acetates Solution
Class: 3
Packing group: III
Labels: Flammable Liquid

SEA TRANSPORT (IMDG):

UN No.: 1123
Proper Shipping Name: BUTYL ACETATES SOLUTION
Class: 3
Packing group: III
Emergency Schedule: F-E
(EmS): S-D
Labels: Flammable liquid

ROAD / RAIL (ADR/RID) / US DOT (49 CFR 172.101) / CANADA TDG:

UN No.: 1123
Proper Shipping Name: Flammable Liquid, n.o.s. (Butyl acetates Solution)
Class: 3
Packing group: III
Labels: 3

SECTION 15. REGULATORY INFORMATION

CHEMICAL INVENTORIES:

TSCA:	All ingredients are on the inventory.
DSL:	All ingredients are on the inventory.
EINECS:	All ingredients are on or exempted from the inventory.
AICS:	All ingredients are on the inventory.
IECSC:	All ingredients are on the inventory.
MITI:	All ingredients are on the inventory.
CSNN:	All ingredients are on the inventory.
PICCS:	All ingredients are on the inventory.
NZIoC:	All ingredients are on the inventory.
KECL:	All ingredients are on the inventory.

CANADA

This product has been classified in accordance with the hazard criteria of the CPR, and this MSDS contains all the information required by the CPR.

**WHMIS Classification: CLASS B - Division 2
CLASS D - Division 2B**

USA

EPA SARA Title III Chemical Listings:

Section 302 Extremely Hazardous Substances (40 CFR 355):	None
Section 304 CERCLA Hazardous Substances (40 CFR 302):	None
Section 311/312 Hazard Class (40 CFR 370):	Acute: Yes ; Chronic: Yes ; Fire: Yes ; Pressure: No ; Reactive: No
Section 313 Toxic Chemicals (40 CFR 372):	None

Supplemental State Compliance Information

California

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: **None known.**

Massachusetts / New Jersey / Pennsylvania

<u>Substance</u>	<u>CAS#</u>	<u>Wt%</u>
n-Buty acetate	123-86-4	80-90

HMIS		NFPA	
H	2	3	0
F	3	2	0
R	0	—	—

KOREA

Classification and labelling in accordance with Industrial Safety and Health Law:	No subject chemicals.
Chemicals controlled in accordance with Toxic Chemicals Control Act:	No subject chemicals.
Hazardous Material Safety Management Act:	Classification – Class 4; 2 nd type petroleum – water-soluble liquids Hazardous ranking – Hazardous rank III Signal Word – Keep Away from fire.
Wastes Management Act:	Product should be disposed of in accordance with Waste Management Law Article 12.

EEC

Labelling according to EEC Directive

S-phrases: S51 (Use only in well-ventilated areas)

R-phrases: R10 (Flammable) | R66 (Repeated exposure may cause skin dryness or cracking) | R67 (Vapours may cause drowsiness and dizziness)

GERMANY

Wassergefährdungsklasse (water hazard class) : WGK 1

SECTION 16. OTHER INFORMATION

The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. This data is offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

SDS prepared by: Raj Moonsammy
Address: Siltech Corp
225 Wicksteed Avenue
Toronto, Ontario, Canada M4H 1G5
Telephone: (416) 424-4567

First Issuing Date: November 15, 2012
Revision No.: 1
Latest Revision Date: November 15, 2012

This is the last page.