



DESCRIPTION

Siltech®C-4800 is 65% active silicone defoamer and antifoam for use in water-based coating and ink applications as well as in various water-based industrial formulations.

TYPICAL PROPERTIES

Appearance	Milky white liquid
Viscosity at 25°C	Approx 1,000 – 5,000 cps
Active Content %	65
Diluent	Water
Specific Gravity at 25°C	1.00

APPLICATION & USES

Siltech®C-4800 provides excellent antifoam and de-foaming in water-based inks, paints and coatings applications.

Siltech®C-4800 is also an effective defoamer and antifoam for various water-based industrial formulations and applications that require a strong de-foaming and persistent antifoam.

Typical usage levels are between 0.10% - 1.00% wt based on total formulation.

The product should be mixed well prior to use.

SHELF LIFE

When stored in the original, unopened containers between 10 and 40°C, **Siltech®C-4800** has a shelf life of 12 months from date of manufacture.

PACKAGING

Siltech®C-4800 is supplied in 20kg pails and 200kg drums.

LEGAL DISCLAIMER

Siltech Corporation believes that the information in this technical data sheet is an accurate description of the typical uses of the product. **Siltech Corporation**, however, disclaims any liability for incidental or consequential damages, which may result from the use of the product that are beyond its control. Therefore, it is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Nothing contained herein is to be considered as permission or a recommendation to infringe any patent or any other intellectual property right.

SILTECH[®] is a registered trademark of **Siltech Corporation**, Toronto, Ontario, Canada.