

# SAFETY DATA SHEET

WHMIS 2015 • OSHA HCS (29 CFR 1910.1200) • NOM-018-STPS-2015

# 1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name Product code Chemical Name CAS No.

- 1.2 Recommended use of the chemical and restrictions on use Identified use(s) Uses advised against
- 1.3 Details of the supplier of the Safety Data Sheet Company Identification

Telephone Fax E-Mail (competent person)

Additional Location

Telephone Fax

**1.4 Emergency telephone number** Emergency Phone No.

## 2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Flam. Liq. 3 Acute Tox. 4 – Dermal Acute Tox. 4 - Inhalation Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1 STOT RE 2 - Hearing deterioration

2.2 Label elements Product Name Symbol

> Signal word(s) Hazard statement(s)



WARNING H226: Flammable liquid and vapour. H312: Harmful in contact with skin. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H332: Harmful if inhaled. H373: May cause damage to organs through prolonged or repeated exposure.

Silmer G-222 A 6972.62 Mixture 25036-25-3 / 69669-36-9 / 67762-95-2 / 1330-20-7 / 100-41-4

intermediate use None known

Siltech Corp 225 Wicksteed Ave Toronto, ON Canada M4H 1G5 +1-416-424-4567 +1-416-424-3158 raj@siltech.com

Siltech Corp 3265 Wolfedale Road, Mississauga ON Canada L5C 1V8 +1-905-270-5534 +1-905-270-5816

CANUTECH - TELEPHONE: EMERGENCY USE ONLY +1-613-996-6666

Product: Silmer G-222 A	1-416-424-4567	www.siltech.com SDS #: 6972.62
<pre>Precautionary statement(s)</pre>		<ul> <li>P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P240: Ground/bond container and receiving equipment.</li> <li>P241: Use explosion-proof electrical/ventilating/lighting/equipment.</li> <li>P242: Use only non-sparking tools.</li> <li>P243: Take precautionary measures against static discharge.</li> <li>P260: Do not breathe dust/fume/gas/mist/vapours/spray.</li> <li>P264: Wash hands and exposed skin thoroughly after handling.</li> <li>P271: Use only outdoors or in a well-ventilated area.</li> <li>P272: Contaminated work clothing should not be allowed out of the workplace.</li> <li>P280: Wear protective gloves/protective clothing/eye protection/face protection.</li> <li>P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</li> <li>P333+P313: If skin irritation or rash occurs: Get medical advice/attention.</li> <li>P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.</li> <li>P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.</li> <li>P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P337+P313: If eye irritation persists: Get medical advice/attention.</li> <li>P363: Wash contaminated clothing before reuse.</li> <li>P403+P235: Store in a well-ventilated place. Keep cool.</li> <li>P501: Dispose of contents/container to: Observe Local Regulations.</li> <li>None known</li> </ul>

# 3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Mixtures

Hazardous ingredient(s)	Synonym(s)	%W/W	CAS No.	EC No.	Hazard pictogram(s) and Hazard statement(s)
Phenol; 2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bis[oxirane]	Bisphenol (Epoxy Resin)	30 - 35	25036-25-3	682- 390-8	GHS07 H315, H317, H319
Xylene	Dimethylbenzene	6.5 - 12	1330-20-7	215- 535-7	GHS02, GHS07 H226, H312, H315, H332
Ethylbenzene	EB	0.4 – 5	100-41-4	202- 849-4	GHS02, GHS08, GHS07 H225, H332, H304, H373

# 4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If symptoms persist, obtain medical attention.

SDS #: 6972.62

	Skin Contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If irritation develops
	Eye Contact	and persists, get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue
	Ingestion	rinsing. Get medical attention immediately. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Get medical attention immediately.
4.2	Most important symptoms and effects, both acute and delayed	May cause an allergic skin reaction. Causes skin irritation. Causes severe eye irritation.
4.3	Indication of any immediate medical attention and special treatment needed	No information available.

# 5. SECTION 5: FIRE-FIGHTING MEASURES

Product: Silmer G-222 A

5.1	Extinguishing Media	
	Suitable Extinguishing Media	In case of fire, use water spray, foam, dry powder or CO2
		for extinction. Keep containers cool by spraying with water if exposed to fire.
	Unsuitable Extinguishing Media	Do not use water jet.
5.2	Special hazards arising from the substance or mixture	No information available.
5.3	Advice for fire-fighters	A self contained breathing apparatus and suitable protective
		clothing should be worn in fire conditions.
6. \$	SECTION 6: ACCIDENTAL RELEASE MEA	SURES
~ 4		
6.1	Personal precautions, protective equipment and	Avoid contact with skin, eyes or clothing. Use personal
6.1	Personal precautions, protective equipment and emergency procedures	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.
6.1 6.2		
	emergency procedures	protective equipment as required.
6.2	emergency procedures Environmental precautions	protective equipment as required. Avoid release to the environment.
6.2	emergency procedures Environmental precautions Methods and material for containment and	protective equipment as required. Avoid release to the environment. Caution - spillages may be slippery. Cover spills with inert
6.2 6.3	emergency procedures Environmental precautions Methods and material for containment and cleaning up	protective equipment as required. Avoid release to the environment. Caution - spillages may be slippery. Cover spills with inert absorbent material. Transfer to a container for disposal.
6.2 6.3 6.4	emergency procedures Environmental precautions Methods and material for containment and cleaning up	protective equipment as required. Avoid release to the environment. Caution - spillages may be slippery. Cover spills with inert absorbent material. Transfer to a container for disposal.

7.1 Precautions for safe handling

		only with sufficient ventilation. Wash thoroughly after handling. General hygiene measures for the handling of chemicals are applicable. Keep away from heat, hot
		surfaces, sparks, open flames and other ignition sources. No smoking.
7.2	Conditions for safe storage, including any	Store in a tightly closed container. Keep away from heat
	incompatibilities	and light.
	Storage Temperature	Ambient
	Storage Life	Stable under normal conditions.
	Incompatible materials	Oxidizing agents
7.3	Specific end use(s)	Industrial use

# 8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters
- 8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
Xylene	1330-20-7	100	435	150		
Ethylbenzene	100-41-4	100	435			

8.1.2 Biological limit value

Not established

Avoid contact with skin and eyes. Avoid ingestion. Use

SDS #: 6972.62

8.1.3 PNECs and DNELs

Product: Silmer G-222 A

- 8.2 Exposure controls
- 8.2.1 Appropriate engineering controls

#### Personal protection equipment 8.2.2 Eye/face protection



Skin protection (Hand protection/ Other)



Respiratory protection



Thermal hazards

8.2.3 Environmental Exposure Controls

#### Not established

Provide adequate ventilation when using the material and follow the principles of good occupational hygiene to control personal exposures.

Eye protection with side protection (EN 166)

Wear impervious gloves (EN374). Nitrile rubber, Polyethylene, PVC Wear suitable protective clothing.

Wear suitable respiratory protective equipment if processing involves working in areas where dusts or vapours are likely to be evolved.

None. Avoid release to the environment.

### 9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical

properties Appearance Colourless to yellowish liquid. Odour Odour Threshold pН Melting Point/Freezing Point Initial boiling point and boiling range Flash point (PMCC) Evaporation rate Flammability (solid, gas) Upper/lower flammability or explosive limits Vapour pressure Vapour density Relative density / Specific Gravity (20°C) Solubility(ies) Partition coefficient: n-octanol/water Auto-ignition temperature **Decomposition Temperature** Viscosity (25°C) Explosive properties Oxidising properties

Characteristic odour. Not available. Not available. Not available. Not available. 34°C Not available. Not applicable. Not available. Not applicable. Not applicable.

#### **10. SECTION 10: STABILITY AND REACTIVITY**

10.1	Reactivity
------	------------

- 10.2 **Chemical stability**
- 10.3 Possibility of hazardous reactions
- Conditions to avoid 10.4
- 10.5 Incompatible materials
- 10.6 Hazardous Decomposition Product(s)

Stable under normal conditions. Stable under normal conditions. Will not occur Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Oxidizing agents, Acids, Alkaline Carbon oxides may be formed.

Product: Silmer G-222 A

# **11. SECTION 11: TOXICOLOGICAL INFORMATION**

11.1 Information on toxicological effects

internation on textooregical encode	
Acute toxicity	
Ingestion	Harmful if swallowed.
Inhalation	Harmful by inhalation.
Skin Contact	Causes skin irritation.
Eye Contact	Causes eye irritation.
Effects and Symptoms	
skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye damage.
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT - single exposure	Not classified
STOT - repeated exposure	Repeated and/or prolonged contact may cause: Hearing
	deterioration
Aspiration hazard	Not classified
Delayed and chronic effects	Not available
Calculated acute toxicity estimate (ATE)	Not available

Not available.

Not available.

Not available.

Not available.

Not available.

None known

## **12. SECTION 12: ECOLOGICAL INFORMATION**

12.1 Toxicity
---------------

- 12.2 Persistence and degradability
- 12.3 Bioaccumulative potential
- 12.4 Mobility in soil
- 12.5 Results of PBT and VPVB assessment
- 12.6 Other adverse effects

# 13. SECTION 13: DISPOSAL CONSIDERATIONS

- 13.1 Waste treatment methods
- 13.2 Additional Information

Do not empty into drains; dispose of this material and its container in a safe way. Dispose of contents in accordance with local, state or national legislation.

### 14. SECTION 14: TRANSPORT INFORMATION

- 14.1 UN number
- **14.2** UN proper shipping name
- 14.3 Class

1993 FLAMMABLE LIQUIDS N.O.S. (Xylene Solution) 3 Packing group III

## **15. SECTION 15: REGULATORY INFORMATION**

15.1	<b>EU regulations</b> REACH Registration No.	Polymer exempt / Not available
	Candidate List of Substances of Very High Concern for Authorisation	Possible trace amounts of: (<0.05%): Octamethylcyclotetrasiloxane (CAS# 556-67-2) Decamethylcyclopentasiloxane (CAS# 541-02-6) Dodecamethylcyclohexasiloxane (CAS# 540-97-6)

Product: Silmer G-222 A

#### 15.2 International Inventories

0		Not	Polymer	01
Country	Listed	listed	exempt	Other
United States (TSCA)	$\checkmark$			
Canada (DSL/NDSL)	DSL√			
European Union (EINECS/ELINCS)	$\checkmark$		$\checkmark$	
Australia (AICS)	$\checkmark$			
China (IECSC)	$\checkmark$			
Japan (ENCS)	$\checkmark$			
South Korea (KECI)	$\checkmark$			
Taiwan (TCSI)	$\checkmark$			
New Zealand (NZIoC)		Х		
Philippines (PICCS)		Х		

15.3 National regulations

United States (TSCA)

HMIS (Hazardous Material Information System) NFPA Rating

- 15.4 US State Regulations
- **15.4.1** SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM
- **15.4.2** SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER

TSCA Inventory Status : All chemicals in this product comply with TSCA rules and regulations including TSCA Section 5 (Inventory Rules). H = 2(5 - 3/8 = 0)

SDS #: 6972.62

$$H = 2/F = 3/R = 0$$
  
 $H = 2/F = 3/R = 0$ 

Specific Listing(s) not required Possible trace amounts of: Ethylene Oxide (CAS# 75-21-8) < 1 ppm

Ethylbenzene (CAS# 100-41-4) 0.4 – 5% Specific Listing(s) not required Possible trace amounts of: Ethylene Oxide (CAS# 75-21-8) < 1 ppm 1,4-Dioxane (CAS# 123-91-1) < 1 ppm

**15.4.3** State Right to Know Lists

Xylene (CAS# 1330-20-7) 6.5 – 12% Ethylbenzene (CAS# 100-41-4) 0.4 – 5% Specific Listing(s) not required Possible trace amounts of: Ethylene Oxide (CAS# 75-21-8) < 1 ppm 1,4-Dioxane (CAS# 123-91-1) < 1 ppm

#### **16. SECTION 16: OTHER INFORMATION**

#### Revision: November 29, 2018

#### LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
STOT	Specific Target Organ Toxicity
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative

#### **References:**

Product: Silmer G-222 A

#### Hazard statement(s) and Precautionary statement(s)

H226: Flammable liquid and vapour.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H373: May cause damage to organs through prolonged or repeated exposure:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/container to: Observe Local Regulations.

Hazard pictogram(s) and Hazard Symbol



#### **Additional Information**

#### Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Siltech Corp. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Siltech Corp. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.