

SAFETY DATA SHEET

WHMIS 2015 • OSHA HCS (29 CFR 1910.1200) • NOM-018-STPS-2015

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name Siltech C-215

Product code 2852 Chemical Name Mixture

CAS No. 189354-72-1 / 1330-20-7 / 100-41-4

1.2 Recommended use of the chemical and

restrictions on use

Identified use(s)

An intermediate chemical product.

Coatings, Additive

Uses advised against None known

1.3 Details of the supplier of the Safety Data Sheet

Company Identification Siltech Corp

225 Wicksteed Ave

Toronto, ON Canada M4H 1G5

 Telephone
 +1-416-424-4567

 Fax
 +1-416-424-3158

 E-Mail (competent person)
 raj@siltech.com

Additional Location Siltech Corp

3265 Wolfedale Road,

Mississauga ON Canada L5C 1V8

Telephone +1-905-270-5534 Fax +1-905-270-5816

1.4 Emergency telephone number

Emergency Phone No. CANUTECH - TELEPHONE: EMERGENCY USE ONLY

+1-613-996-6666

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Flam. Liq. 3

Acute Tox. 4 – Dermal Acute Tox. 4 - Inhalation

Skin Irrit. 2

STOT RE 2 - Hearing deterioration

Asp. Tox. 1

2.2 Label elements

Product Name Siltech C-215

Symbol



Signal word(s) DANGER

Hazard statement(s) H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin. H315: Causes skin irritation. H332: Harmful if inhaled.

H373: May cause damage to organs through prolonged or

repeated exposure.

Precautionary statement(s) P210: Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof

electrical/ventilating/lighting/equipment.

Product: Siltech C-1215 SDS #: 2852

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust/fume/gas/mist/vapours/spray. P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331: Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

P363: Wash contaminated clothing before reuse. P403+P235: Store in a well-ventilated place. Keep cool. P501: Dispose of contents/container to: Observe Local Regulations.

Other hazards 2.3

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Mixtures

| | | | | | Hazard pictogram(s) and | |
|-------------------------|-----------------|---------|-----------|-----------|-------------------------|--|
| Hazardous ingredient(s) | Synonym(s) | %W/W | CAS No. | EC No. | Hazard statement(s) | |
| Xylene | Dimethylbenzene | 75 - 85 | 1330-20-7 | 215-535-7 | GHS02, GHS07 | |
| | | | | | H226, H312, H315, H332 | |
| Ethylbenzene | EB | 10 - 15 | 100-41-4 | 202-849-4 | GHS02, GHS08, GHS07 | |
| Luiyiberizerie | | | | | H225, H332, H304, H373 | |

None known

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation IF INHALED: Remove person to fresh air and keep comfortable

for breathing. If symptoms persist, obtain medical attention. Skin Contact IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If irritation develops

and persists, get medical attention.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation develops and persists, get medical attention. Ingestion IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Get

medical attention immediately.

Causes skin irritation. May cause irritation to the respiratory 4.2 Most important symptoms and effects, both system. Hearing deterioration. acute and delayed

4.3 Indication of any immediate medical No information available.

attention and special treatment needed

Revision: 2 Date: 14/12/2018 Page: 2/7

Product: Siltech C-1215 SDS #: 2852

5. SECTION 5: FIRE-FIGHTING MEASURES

5.1 **Extinguishing Media**

> Suitable Extinguishing Media In case of fire, use water spray, foam, dry powder or CO2

> > for extinction. Keep containers cool by spraying with water if

exposed to fire.

Unsuitable Extinguishing Media

Special hazards arising from the substance or

mixture

5.2

Do not use water jet. No information available.

5.3 Advice for fire-fighters A self contained breathing apparatus and suitable protective

clothing should be worn in fire conditions.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and Avoid contact with skin, eyes or clothing. Use personal

emergency procedures protective equipment as required. **Environmental precautions** 6.2 Avoid release to the environment.

6.3 Methods and material for containment and Caution - spillages may be slippery. Cover spills with inert cleaning up

absorbent material. Transfer to a container for disposal.

See Section: 7 & 8. 6.4 Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling Avoid contact with skin and eyes. Avoid ingestion. Use

> only with sufficient ventilation. Wash thoroughly after handling. General hygiene measures for the handling of chemicals are applicable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

7.2 Conditions for safe storage, including any

incompatibilities

Store in a tightly closed container. Keep away from heat and light.

Ambient

Storage Temperature

Storage Life Stable under normal conditions.

Incompatible materials Oxidizing agents Specific end use(s) Industrial use

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

7.3

8.1.1 **Occupational Exposure Limits**

| | | LTEL (8 hr TWA | LTEL (8 hr TWA | STEL | STEL | |
|--------------|-----------|----------------|----------------|-------|---------|------|
| SUBSTANCE | CAS No. | ppm) | mg/m³) | (ppm) | (mg/m³) | Note |
| Xylene | 1330-20-7 | 100 | 435 | 150 | | |
| Ethylbenzene | 100-41-4 | 100 | 435 | | | |

8.1.2 Biological limit value Not established

8.1.3 PNECs and DNELs Not established

8.2 **Exposure controls**

Appropriate engineering controls Provide adequate ventilation when using the material and 8.2.1

follow the principles of good occupational hygiene to control

personal exposures.

Personal protection equipment

Eye protection with side protection (EN 166) Eye/face protection

Skin protection (Hand protection/ Other) Wear impervious gloves (EN374).

Nitrile rubber, Polyethylene, PVC

Product: Siltech C-1215 SDS #: 2852



Wear suitable protective clothing.

Respiratory protection



Wear suitable respiratory protective equipment if processing involves working in areas where dusts or vapours are likely

to be evolved.

Thermal hazards None.

8.2.3 Environmental Exposure Controls Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical

properties

Appearance Colourless to yellowish liquid.

Odour
Odour Characteristic odour.
Odour Threshold
PH
Not available.
Melting Point/Freezing Point
Not available.
Initial boiling point and boiling range
Flash point (PMCC)
S4°C
Characteristic odour.
Not available.
Not available.
34°C

Evaporation rate

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Vapour pressure

Vapour density

Not available.

Not available.

Not available.

Not available.

Relative density / Specific Gravity (20°C) 0.89

Solubility(ies)

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition Temperature

Viscosity (25°C)

Insoluble in water.

Not available.

Not available.

3 cps

Explosive properties Not applicable.
Oxidising properties Not applicable.

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity Stable under normal conditions.
 10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Will not occur

10.4 Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

10.5 Incompatible materials
 10.6 Hazardous Decomposition Product(s)
 Oxidizing agents, Acids, Alkaline
 Carbon oxides may be formed.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

IngestionHarmful if swallowed.InhalationHarmful by inhalation.Skin ContactCauses skin irritation.Eye ContactMay cause eye irritation.

Effects and Symptoms

skin corrosion/irritation

Serious eye damage/irritation

Respiratory or skin sensitization

May cause eye irritation.

May cause respiratory irritation.

May cause respiratory irritation.

Germ cell mutagenicity Not classified

Revision: 2 Page: 4/7 Date: 14/12/2018

Product: Siltech C-1215 SDS #: 2852

 Carcinogenicity
 Not classified

 Reproductive toxicity
 Not classified

 STOT - single exposure
 Not classified

STOT - repeated exposure Repeated and/or prolonged contact may cause: Hearing

deterioration Not classified

Aspiration hazard Not classified Delayed and chronic effects Not available Calculated acute toxicity estimate (ATE) Not available

12. SECTION 12: ECOLOGICAL INFORMATION

12.1 **Toxicity** Not available. Persistence and degradability Not available. 12.2 Bioaccumulative potential Not available. 12.3 Mobility in soil Not available. 12.4 Results of PBT and VPVB assessment Not available. 12.5 Other adverse effects None known

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods Do not empty into drains; dispose of this material and its

container in a safe way.

13.2 Additional Information Dispose of contents in accordance with local, state or

national legislation.

14. SECTION 14: TRANSPORT INFORMATION

14.1 UN number 1993

14.2 UN proper shipping name FLAMMABLE LIQUIDS N.O.S. (Xylene Solution)

14.3 Class 3 Packing group III

15. SECTION 15: REGULATORY INFORMATION

15.1 EU regulations

REACH Registration No. Polymer exempt / Not available

Candidate List of Substances of Very High Possible trace amounts of: (<0.05%):

Concern for Authorisation Octamethylcyclotetrasiloxane (CAS# 556-67-2)

Decamethylcyclopentasiloxane (CAS# 541-02-6) Dodecamethylcyclohexasiloxane (CAS# 540-97-6)

15.2 International Inventories

| | | Not | Polymer | |
|--------------------------------|----------|--------|---------|-------|
| Country | Listed | listed | exempt | Other |
| United States (TSCA) | ✓ | | | |
| Canada (DSL/NDSL) | NDSL√ | | | |
| European Union (EINECS/ELINCS) | ✓ | | ✓ | |
| Australia (AICS) | ✓ | | | |
| China (IECSC) | ✓ | | | |
| Japan (ENCS) | ✓ | | | |
| South Korea (KECI) | √ | | | |
| Taiwan (TCSI) | √ | | | |
| New Zealand (NZIoC) | | X | | |
| Philippines (PICCS) | | Χ | | |
| | | | | |

Product: Siltech C-1215 SDS #: 2852

National regulations

United States (TSCA) TSCA Inventory Status: All chemicals in this product comply

with TSCA rules and regulations including TSCA Section 5

(Inventory Rules).

HMIS (Hazardous Material Information System) H = 2/F = 3/R = 0H = 2/F = 3/R = 0

NFPA Rating

US State Regulations

15.4.1 SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR

OTHER REPRODUCTIVE HARM

Specific Listing(s) not required Possible trace amounts of:

Ethylene Oxide (CAS# 75-21-8) < 1 ppm

15.4.2 SUBSTANCES KNOWN TO THE STATE OF

CALIFORNIA TO CAUSE CANCER

Ethylbenzene (CAS# 100-41-4) 10 - 15%

Specific Listing(s) not required Possible trace amounts of:

Ethylene Oxide (CAS# 75-21-8) < 1 ppm 1,4-Dioxane (CAS# 123-91-1) < 1 ppm

15.4.3 State Right to Know Lists

Xylene (CAS# 1330-20-7) 75 - 85% Ethylbenzene (CAS# 100-41-4) 10 - 15%

Specific Listing(s) not required Possible trace amounts of:

Ethylene Oxide (CAS# 75-21-8) < 1 ppm 1,4-Dioxane (CAS# 123-91-1) < 1 ppm

16. SECTION 16: OTHER INFORMATION

Revision: December 14, 2018

LEGEND

LTEL Long Term Exposure Limit STEL Short Term Exposure Limit STOT Specific Target Organ Toxicity Derived No Effect Level DNEL

PNEC Predicted No Effect Concentration PBT Persistent, Bioaccumulative and Toxic vPvB very Persistent and very Bioaccumulative

Hazard statement(s) and Precautionary statement(s)

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H373: May cause damage to organs through prolonged or repeated exposure:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331: Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

Revision: 2 Date: 14/12/2018 Page: 6/7

Product: Siltech C-1215 SDS #: 2852

P363: Wash contaminated clothing before reuse.

P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/container to: Observe Local Regulations.

Hazard pictogram(s) and Hazard Symbol



Additional Information

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Siltech Corp. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Siltech Corp. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Revision: 2 Page: 7/7 Date: 14/12/2018