



PERFORMANCE INSPIRED INGENUITY

Siltech Corporation  
225 Wicksteed Avenue  
Toronto, Ontario M4H 1G5

[www.siltech.com](http://www.siltech.com)

[Sales@siltech.com](mailto:Sales@siltech.com)  
+1 416.424.4567

## **Lustrous Founding Lite**

### Foundation

#### Description:

Lustrous Founding Lite is a variation on our Lustrous Founding foundation formulation. The “Lite” variation features only one silicone ingredient, **Siltech® PTM**. **Siltech® PTM** is a phenyl-modified silicone fluid that excels as a compatibilizer and adds gloss to makeup. **Siltech® CE-2000** is a versatile citrate ester that effectively disperses pigments while additionally imparting both cushion and emolliency. Lustrous Founding Lite exhibits uniform pigment dispersion, applies easily and finishes with a light, silky texture.

#### Ingredients:

Phase	Ingredients	INCI name	Weight %
A	D.I. Water	Water	45.84
	Zemea (DuPont)	Propanediol	5.00
	NaCl	Sodium Chloride	1.00
B	<b>Siltech CE-2000 (Siltech)</b>	Trioctyldodecyl Citrate	6.00
	Eutanol G (BASF)	Octyldodecanol	5.00
	Dehymuls PGPH (BASF)	Polyglyceryl-2 Dipolyhydroxystearate	4.50
	<b>Siltech PTM (Siltech)</b>	Phenyl Trimethicone	7.00
	JeeChem CTG (Jeen)	Caprylic/Capric Triglyceride	4.50
	Jarcane 12 (Jarchem)	Dodecane	10.00
	Shea Butter (Hallstar)	Butyrospermum Parkii (Shea) Butter	1.00
C	Crodacol C-95 (Croda)	Cetyl Alcohol	2.00
	Unipure White LC 987 AS-EM (Sensient)	CI 77891 (and) Triethoxycaprylylsilane	4.32
	Unipure Yellow LC182 AS-EM (Sensient)	CI 77492 (and) Triethoxycaprylylsilane	0.65
	Unipure Red LC381 AS-EM (Sensient)	CI 77491 (and) Triethoxycaprylylsilane	0.31
	Unipure Black LC989 AS-EM (Sensient)	CI 77499 (and) Triethoxycaprylylsilane	0.04
D	Dry-Flo Elite BN (AkzoNobel)	Aluminum Starch Octenylsuccinate (and) Boron Nitride	2.34
	Symocide PS (Symrise)	Phenoxyethanol, Decylene Glycol (and) 1,2-Hexanediol	0.50
Total			100.00



*PERFORMANCE INSPIRED INGENUITY*

Siltech Corporation  
225 Wicksteed Avenue  
Toronto, Ontario M4H 1G5

[www.siltech.com](http://www.siltech.com)

[Sales@siltech.com](mailto:Sales@siltech.com)  
+1 416.424.4567

Procedure:

- 1) Combine ingredients in Phase B, heat up to 80°C and mix well.
- 2) Combine ingredients in Phase C, add to Phase B and blend well.
- 3) Combine ingredients in Phase A, mix well. Add Phase A slowly to batch under moderate mixing rate.
- 4) Add preservative, Phase D, under mixing and mix well. High shear for 30 minutes.

Product formulations are included as illustrative examples. Siltech Corporation makes no representation or warranty of any kind with regard to any such formulations, including, without limitation, concerning the efficacy or safety of any product manufactured using such formulations.

3/5/24